


FOLDJET 2000




FOLDJET 2000, a professional offline folder, impresses:

- with its versatile folding programs, even the folding width is adjustable in 1mm/0.04" increments
- with its speed and precision
- with its easy operation
- with its reliable and proven technology
- with its attractive design
- with its excellent roi: even for small folding requirements



● ● ● Made in Germany

Simple touchpad operation



With a touch of a key select DIN-Format A3 to A0, free formats, all with or without binding edge or packet folds, then insert the media. That's all! The display shows the current setting and also diagnostic messages!

Quick and easy fan folding



At approx. 12m/min (40 ft./min.) the FOLDJET 2000 folds your drawings quickly and very precisely. Media up to 920 mm (36") wide and up to 30 m (100 ft.) in length can be processed.




Optional table extension.

Technical and performance data:

Folding material:	Max. width: 920 mm (36"), max. length: 30 m (100 ft.) Material: opaque paper: 70 to 110 g/m ² , E size (20 lb. Bond) (e.g. diazo, ppc or plotting paper)
Folding length:	DIN-Folding: A3 to A0 with/without binding edge US-Architect/Engineer B to E with/without binding edge Packet folding (190/210): 95 to 330/350 mm (4 to 13/14") Free format (190): 95 to 330 mm with/without binding edge (4 to 13") Free format (210): 95 to 330 mm without binding edge (4 to 13") Binding edge: 10 to 50 mm (0.4 to 2")
Cross folding:	Automatic detection Length: 95 to 350 mm (4 to 14") Max. Format: DIN A0 (80g/m ²) E size (20 lb. Bond)
Folding speed:	Approx. 12m/min (40 ft./min)
Settings:	All folds are adjustable in 1 mm (0.04") increments
Display languages:	German, English, French, Italian, Dutch, Swedish
Length dimensions:	mm or inch
Service:	Automatic diagnosis system
Optional table extensions:	Extension increases table width to 1236 mm (49") Extension increases table length to 1044 mm (41")
Measurements:	Width: 1128 mm (44.5") Length (with table): 1395 mm (55") Length table down: 715 mm (28") Total height: 1030 mm (40") Working height: 910 mm (36")
Weight:	Net approx. 168 kg (370 lbs.)
Power:	230 V ±10%, 50-60 Hz, 250 W 115 V ±10%, 50-60 Hz, 250 W
Safety standards:	CE

... and cross folds



Automatic crossfold detection. Folded drawings stack neatly in the output tray to provide a complete folding solution. Cross folds up to DIN A0.

Minimal space requirement



FOLDJET 2000 uses less than 1m² with the table down for storage and only 1.6 m² in operation.

BASYS GmbH

Wilhelm-Fressel-Str. 4
21337 Lüneburg

Tel. +49 (0) 41 31/95 23-0
Fax +49 (0) 41 31/95 23-99
sales@basys-web.de
www.basys-web.de

● ● ● Made in Germany